

CG500



Cummins Silent Generator

Performance

- Carefully selected components
- Accurately developed and tested configuration

Quality Control

- International standard testing procedure
- Professional manufacture team

Service efficiency

- Humanization design and improvements
- Superior accessibility to all service points

Increased transport efficiency

- Compact and safe concept
- Sturdy design

Superior resale value

- Designed and built to last

Technical Data

Genset Model		CG500
Frequency		50 Hz
Rated speed	r/min	1500 rpm
Rated power factor (lagging)		0.8
Rated prime power	kVA	500/400
Rated standby power	kVA	550/440
Rated voltage line to line	V	380/220
Rated current	A	759.7
Maximum sound power level	dB(A)	75
Fuel consumption at 75%	L/H	82
Fuel consumption at 100%	L/H	107
Fuel tank capacity	L	830

Engine Model		KTA19-G4
Rated net power prime	kW	448
Rated net power standby	kW	504
Cooling way		Water
Number of cylinders		6
Arrangement		In-line
Bore & Stroke	mm	159x159
Compression ratio		14.5:1
Displacement	L	18.9
Oil capacity	L	36
Charging alternator	V	24
Start motor	V	24

Alternator-Stamford

Model		HCI544C
Voltage	V	380/220
Frequency	Hz	50
Prime Capacity	kVA	500
Prime Power	kW	400
Power input	kW	426
Phase no.		3
Power factor		0.8
Voltage regulation	%	±0.5
Protection grade		IP23
Insulation grade		Class H

Dimension

Length*width*height	mm	4800x1600x2400
Net weight	kg	4300
Gross weight	kg	4350


Controller-Deepsea DSE3110

Standard function	
Engine control	Generator monitoring
Generator protection	Specification display
Display	
Frequency	Battery voltage
Running hour	
Warning/shutdown	
Under/over voltage	Under/over speed
Under/over frequency	Low oil pressure
High/low battery voltage	High water temperature
Communication modules	
USB	


Controller-Deepsea DSE6020

Standard function	
Engine control	Generator monitoring
Generator protection	Specification display
Display	
Voltage	Current
Frequency	Fuel level
Oil pressure	Rated power
Running hour	Battery voltage
Warning/shutdown	
Under/over voltage	Under/over speed
Under/over frequency	Low oil pressure
High/low battery voltage	High water temperature
Communication modules	
RS232, RS485, S-USB	

This generator does comply with EU requirements related to working environment, regulations concerning safety and emissions as well with the outdoor noise directive 2000/14/EC.

PT. SURYA PUTRA MESINDO

Address : Jl. Kamal Raya Outer Ring Road,
 Taman Palem Lestari, Ruko Galaxy Blok N No.17,18,19
 Cengkareng - Jakarta Barat 11730 INDONESIA
 Phone : (021) 5595-9133 (Hunting)
 Fax : (021) 5595-9132
 E-mail : suryaputra@indo.net.id
 Website : www.suryaputra.co.id