

# CG315



## Cummigen Silent Generator

### Performance

- Carefully selected components
- Accurately developed and tested configuration

### Quality Control

- International standard testing procedure
- Professional manufacture team

### Service efficiency

- Humanization design and improvements
- Superior accessibility to all service points

### Increased transport efficiency

- Compact and safe concept
- Sturdy design

### Superior resale value

- Designed and built to last

## Technical Data

Genset Model		CG315
Frequency		50 Hz
Rated speed	r/min	1500 rpm
Rated power factor (lagging)		0.8
Rated prime power	kVA	312.5/250
Rated standby power	kVA	350/280
Rated voltage line to line	V	380/220
Rated current	A	474.8
Maximum sound power level	dB(A)	75
Fuel consumption at 75%	L/H	44
Fuel consumption at 100%	L/H	61
Fuel tank capacity	L	500

Engine Model		NTA855-G1B
Rated net power prime	kW	250
Rated net power standby	kW	290
Cooling way		Water
Number of cylinders		6
Arrangement		In-line
Bore & Stroke	mm	140x152
Compression ratio		14.5:1
Displacement	L	14
Oil capacity	L	39.6
Charging alternator	V	24
Start motor	V	24

### Alternator-Stamford

Model		HCI444ES
Voltage	V	380/220
Frequency	Hz	50
Prime Capacity	kVA	325
Prime Power	kW	260
Power input	kW	274
Phase no.		3
Power factor		0.8
Voltage regulation	%	±0.5
Protection grade		IP23
Insulation grade		Class H

### Dimension

Length*width*height	mm	4200x1400x2100
Net weight	kg	2750
Gross weight	kg	3800



### Controller-Deepsea DSE3110

Standard function	
Engine control	Generator monitoring
Generator protection	Specification display
Display	
Frequency	Battery voltage
Running hour	
Warning/shutdown	
Under/over voltage	Under/over speed
Under/over frequency	Low oil pressure
High/low battery voltage	High water temperature
Communication modules	
USB	



### Controller-Deepsea DSE6020

Standard function	
Engine control	Generator monitoring
Generator protection	Specification display
Display	
Voltage	Current
Frequency	Fuel level
Oil pressure	Rated power
Running hour	Battery voltage
Warning/shutdown	
Under/over voltage	Under/over speed
Under/over frequency	Low oil pressure
High/low battery voltage	High water temperature
Communication modules	
RS232, RS485, S-USB	

*This generator does comply with EU requirements related to working environment, regulations concerning safety and emissions as well with the outdoor noise directive 2000/14/EC.*

## PT. SURYA PUTRA MESINDO

**Address :** Jl. Kamal Raya Outer Ring Road,  
Taman Palem Lestari, Ruko Galaxy Blok N No.17,18,19  
Cengkareng - Jakarta Barat 11730 INDONESIA  
Phone : (021) 5595-9133 (Hunting)  
Fax : (021) 5595-9132  
E-mail : [suryaputra@indo.net.id](mailto:suryaputra@indo.net.id)  
Website : [www.suryaputra.co.id](http://www.suryaputra.co.id)